




2.5Gbps APD Chip for GPON Application

P/N: DO323_55um_APD



Known Good Die

PRELIMINARY DATASHEET



Introduction

This high performance product is a 2.5G APD (avalanche photodiode) chip that features a large 55 μ m front-side illuminated detection window for easy optical assembly. This product has an excellent reliability and gain at operating voltage, and high sensitivity up to -34dBm with a low-noise TIA. It is designed primarily to be used at 1310nm and 1490nm APD-TIA GPON applications that enable data transmission for today's fiber-to-the-home (FTTH) market.

Key Features

- GCS proprietary design and process technologies
- 55 μ m optical detection window
- Backside common cathode and topside anode
- -34dBm typical sensitivity with low-noise TIA
- -40 $^{\circ}$ C to 85 $^{\circ}$ C operation range
- High reliability with GCS robust 4" wafer manufacturing with fast cycle-time
- Deliverable in GCS Known Good Die™ with 100% testing and inspection
- Customized layout dimensions available
- RoHS compliant

Applications

- 2.5Gbps GPON receiver
- SONET OC48
- Ethernet

SPECIFICATIONS (T=25C $^{\circ}$)

	Conditions	Min.	Typical	Max.	Unit	Notes
Responsivity	1550 nm, M=1	-	0.87	-	A/W	
Gain	V _{br} -2V, P _o =1uW		9		-	
Response Current	1550 nm, V _{br} -2V, P _o =1uW	6	8		uA	
Breakdown voltage (V _{br})	I _d =10uA, P _o =1uW	40	45	50	V	
Temperature coefficient of V _{br}	-45 $^{\circ}$ C~+80 $^{\circ}$ C	0.06	0.08	0.10	V/ $^{\circ}$ C	
Dark current	V _{br} -2V	-	40	100	nA	
Bandwidth	V _{br} -2V, P _o =1uW, 25 $^{\circ}$ C	2.5	-	5	GHz	
Capacitance	V _{br} -2V, f=1 MHz, 25 $^{\circ}$ C	-	0.37	0.6	pF	
Wavelength Range		1200	1490	1600	nm	
Recommended operation bias			V _{br} -2V		V	
Recommended alignment bias	25 $^{\circ}$ C		V = V _{br} -6V		V	
Operating bias range (V)	25 $^{\circ}$ C	6	15		V	

Global Communication Semiconductors, LLC

23155 Kashiwa Court, Torrance, CA 90505

Tel: (310) 530-7274 Fax: (310) 517-8200 e-mail: info@gcsincorp.com

www.gcsincorp.com




Known Good Die

ABSOLUTE MAXIMUM RATING


Parameter	Rating
Operating Temperature	-40°C to 85°C
Storage Temperature	-40°C to 125°C
Soldering Temperature	260°C / 10 sec
Forward Current	5mA
Reverse Current	3mA

DIMENSIONS

(Unit: μm)	Min.	Typical	Max.
Detection window		55	
Bonding pad diameter		75	
Die height	140	150	160
Die width	290	300	310
Die length	290	300	310



Typical Performance at 25°C



Dark Current and Photo Current vs. Voltage at 25°C

Global Communication Semiconductors, LLC

23155 Kashiwa Court, Torrance, CA 90505

Tel: (310) 530-7274 Fax: (310) 517-8200 e-mail: info@gcsincorp.com

www.gcsincorp.com